

**IN THE CLAIMS:**

Please amend the claims as follows:

Claim 1 (Currently Amended): Apparatus for chip removing machining comprising a first part and a second part coupled together by a coupling, wherein the coupling comprises two interacting surfaces and a clamping member for forcing the surfaces together, the interacting surfaces being profiled with male and female members, respectively that are intercoupled to establish a firm locking of the first and second parts against each other, said coupling defining a longitudinal center line, wherein the first and the second parts are provided with aligned holes for receiving the clamping member, wherein the male and the female members are oriented on the interacting surfaces such that the male and female members intercouple only in a single position, the orientation of the male and female members prevents the male and female members from intercoupling in another position.

Claim 2 (Original): The apparatus according to claim 1 wherein the male and female members are spaced from the center line.

Claim 3 (Original): The apparatus according to claim 1 wherein the first part includes a channel for cooling medium, the channel defines a fluid exit port in an envelope surface of the first part.

Claim 4 (Original): The apparatus according to claim 1 wherein the male and female members extend orthogonally relative to the center axis.

Claim 5 (Previously Presented): The apparatus according to claim 1 wherein one of the first and second parts comprises a turning tool having only a single active cutting edge, wherein incorrect positioning of the cutting edge is prevented by the male and female members being intercoupled in the single position.

Claim 6 (Original): The apparatus according to claim 1 wherein the male and female members are arranged asymmetrically with respect to the center hole.

Claim 7 (Original): The apparatus according to claim 6 wherein the first part includes a channel for cooling medium, the channel defining a fluid exit port in an envelope surface of the first part.

Claim 8 (Currently Amended): A cutting head for chip removing machining comprising a head surface adapted to intercouple with a holder surface of a holder; a center through-hole formed in the cutting head and extending through the head surface and defining a center axis intersecting the head surface, the head surface having an axially irregular surface profile defined by portions extending axially to different extents than other portions thereof, the axially irregular surface profile ~~presenting a first configuration~~ adapted to be received in a corresponding axially irregular ~~surface profile configuration~~ of the holder surface at a first angular position about the

center axis with respect to the holder surface; wherein the configurations presented by surface profile of the head surface precludes reception thereof in the surface profile of the holder surface at [[in]] all other angular positions thereof about the axis are different from the first configuration, whereby such that the head surface and the holder surface intercouple defines only in a single position of intercoupling and no other position.

Claim 9 (Currently Amended): A holder adapted to be coupled with a cutting head for chip removing machining comprising a holder surface adapted to intercouple with a head surface of the cutting head; a center hole formed in the holder and extending through the holder surface and defining a center axis intersecting the holder surface, the holder surface having an axially irregular surface profile defined by portions extending axially to different extents than other portions thereof, the axially irregular surface profile ~~presenting a first configuration~~ adapted to be received in a corresponding axially irregular surface profile configuration of the head surface at a first angular position about the center axis with respect to the head surface; wherein the configurations presented by surface profile of the holder surface precludes reception thereof in the surface profile of the head surface at [[in]] all other angular positions thereof about the axis is different from the first configuration, whereby such that the holder surface and the head surface intercouple defines only in a single position of intercoupling and no other position.